

SabreSeal™ MB

SabreSeal MB is a one component, non-drying polybutene rubber based mastic that does not harden but rather remains permanently soft and paste-like. SabreSeal MB has excellent resistance to water vapour transmission.

Features

- Permanently non-skinning
- Low shrinkage
- Moisture resistance
- Excellent adhesion

Uses

It's suitable for all kinds of plastics, metals, glass, masonry and timber. It also can be used in the installation of coolrooms and prefabricated construction.



Limitations

- Should not be applied in exposed joints
- Not for use in areas subject to dynamic stress
- Not for mobile homes, truck bodies

Colour

White, Almond. Other colours are available upon request.

Specification

Form	Non-Sagging Paste
Colour	White
Specific Gravity	1.60 ± 0.05
Slump	2.5 mm Maximum
Shrinkage	5 % Maximum
Service Temperature	- 40° C to 80° C

Application

- Surface must be clean and dry
- Cut nozzle to desired size
- Insert cartridge into caulking gun
- Push sealant ahead for uniform bead
- Clean off excess sealant with kerosene or mineral spirits

Caution

Read and understand Material Safety Data Sheet before handling or using this product. We recommend preliminary compatibility tests prior to application to achieve desirable results. This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

Reviewed January 2023
SabreSeal_MB_TDS_2301

IMPORTANT NOTICE

Sabre Adhesives Limited makes no warranties, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application. Due to the fact that specific substrates, such as: plastics, polycarbonates, etc, may differ from manufacturer to manufacturer we recommend preliminary compatibility tests. Please remember that many factors can affect the use and performance in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a product. Given the variety of factors that can affect the use of our products some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

LIMITATION OF REMEDIES AND LIABILITY

If the product is proved to be defective, the sole remedy shall be to refund the purchase price or to repair or replace the defective product. Sabre shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

New Zealand

+64 6 366 0007
40-42 Cambridge St South
Levin 5510

Australia

+61 2 9098 8244
Level 6, 10 Herb Elliott Ave
Sydney Olympic Park, NSW 2127