

BPIR – Building Production Information Requirements SabreSeal NC45 Facade Silicone

Declaration

Sabre Adhesives Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product Name	Product Code		
SabreSeal NC45 Facade Silicone Matt Black 300ml	1400154		
SabreSeal NC45 Facade Silicone Matt Grey 300ml	1400152		
SabreSeal NC45 Facade Silicone Matt White 300ml	1400151		
SabreSeal NC45 Facade Silicone Matt Black 600ml	1400155		
SabreSeal NC45 Facade Silicone Matt Grey 600ml	1400162		
SabreSeal NC45 Facade Silicone Matt White 600ml	1400153		

Product Description

SabreSeal NC45 is a non-slumping high performance, 100% neutral cure silicone sealant designed for façade cladding, commercial weathersealing and glazing applications. It is a single component elastomeric sealant that is permanently elastic upon curing and has a movement capability of ±50 %.

Scope Of Use

SabreSeal NC45 has been developed specifically for sealing aluminium composite panels in external applications that experience high climatic exposure. Its superior adhesion performance and high durability make it well suited for glazing and cladding applications.

Limitations

SabreSeal NC45 is not recommended for following applications:

- Structural glazing applications.
- Below waterline or permanent water immersion.
- Traffic areas subject to abrasion.
- Polycarbonate and polyacrylate, if under tension.
- Applications that requires the sealant to be painted.
- Neoprene rubber

Conditions Of Use

Installation of SabreSeal NC45 should be carried out by a competent professional, in accordance with the manufacturer's installation instructions.

The responsibility for using this product in accordance with the application's requirements rests with the user. We recommend consulting our Technical Data Sheet, available at www.sabreadhesives.com

Contribution To Building Code Clauses:

Relevant Code Clauses	Contributions to compliance	
B2 Durability — B2.3.1 (a)	Clause B2 DURABILITY: Performance E2.3.2 (b), 15 years	
	and B2.3.1 (c), 5 years, SabreSeal NC45 will achieve a	
	minimum of 15 years of performance.	

E2 External Moisture:	Performance E2.3.2. When used as part a suitable
	cladding system, SabreSeal NC45 will contribute to
	meeting this requirement.
F2 Hazardous building	Performance F2.3.1 SabreSeal NC45 does not present a
materials	health hazard to people. And satisfies this
	requirement.

Documentation:

For supporting information refer to

https://www.sabreadhesives.com/product/sabreseal-nc45-facade-silicone-sealant/

Contact Details:

		A 11			
COL	bre .	ΛОІ	nacı	\sim 1	TO
2010		=/a		v - 1	444

Legal trading name: Sabre Adhesives Limited

Address: 40-42, Cambridge Street South, Levin 5510, New Zealand

Website: www.sabreadhesives.com

Email: SalesNZ@sabreadhesives.com

Phone number: +64 6 366 0007

NZBN: 9429033154688

Warnings and Bans:

SabreFix NC45 Facade Silicone is not subject to any warnings or bans under section 26 of the Building Act 2004.