

## SabreFix™ BS

SabreFix BS is a solvent-based plastoelastic bituminous sealant, reinforced by fibres for sealing and repairing bituminous surfaces. After curing a permanent flexible mass is formed.

### Benefits

- Immediate and permanent adhesion on all common construction materials (i.e. brick, concrete, lead, zinc, tiles, isolation panels, certain plastics)
- Can be applied under humid conditions
- It is thixotropic and therefore cannot drip, flow or spill and makes no threads
- Free from asbestos.
- Remains flexible after processing and vulcanization
- Moisture resistant
- Economic in use
- Inflammable (when used properly)
- High insulation
- Protects against rust and moisture



### Applications

- Waterproof sealing of joints, seams, chimneys, ventilation tubes, drainpipes
- Adhesive for synthetic materials, tiles, concrete, rubber, insulating panels
- Sealing seams in wooden ships or boats

## Technical Characteristics

<b>Basis</b>	Bitumen
<b>Curing System</b>	Neutral, physical drying
<b>Density</b>	1.25± 0.02 g/ml (ASTM D 792)
<b>Skin Formation</b>	30 min. (23°C and 50% R.H)
<b>Curing Rate</b>	0,5-1 mm/day (23°C and 50% R.H)
<b>Consumption</b>	450 g/m <sup>2</sup>
<b>Application Temperature</b>	+1°C to +30°C

## Instructions

All surfaces should be free from dust or grease. On humid surfaces or in special cases, a preliminary adhesion test is recommended. To be applied with a spatula or by means of a cartridge. It should be applied in strips or spots, for a good evaporation of the solvent.

## Storage & Shelf Life

15 months if stored at room temperature.

## Packaging & Colour



**Available colours:** Black

**Packaging size:** is available in cartons of 24 x 300ml cartridges

## Restrictions

- It cannot be painted with paints on solvent basis
- Can only be used for synthetic materials without softener
- Contact with mineral oils softens the product

## Safety

Mechanically with filling-knife, turpentine or xylene.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

### New Zealand

+64 6 366 0007  
40-42 Cambridge St South  
Levin 5510

### Melbourne

+61 3 8657 5507  
67 Gateway Blvd  
Epping, VIC 3076

### Sydney

+61 2 9098 8244  
Level 6, 10 Herb Elliott Ave  
Sydney Olympic Park, NSW 2127