

SabreGrip™ S10

SabreGrip S10 is a versatile, high performance, industrial grade, spray contact adhesive that has very low VOC's and is CA Compliant. Formulated to have a very high solid content and heat resistance, SabreGrip S10 is designed for bonding decorative laminate to particleboard or MDF and other postforming applications. It has an extremely fine mist spray making it especially ideal for high gloss laminates or thin veneers where telegraphing is an issue. SABRE GRIP S10 may also be used on a variety of other substrates including fabrics, foam, headliners, glass, cork, fibreglass and many plastics.

Storage

Store out of direct sunlight in a dry, well-ventilated area indoors between 5°C and 20°C. Store away from foodstuffs.



Features

- Low VOC
- CA Compliant
- High Temperature Resistance
- Postformable
- Misting Spray
- Long Shelf Life
- Water Resistant
- High Strength Bond
- Low Odour

Shelf Life

1 year from date of manufacture.

Physical Properties

Appearance	Clear
Liquid Specific Gravity	0.93 – 0.95 GMS/CC
Solvent	Methyl Acetate
Shear Adhesion	>100 psi
Shear Adhesion Failure	> 200 °F
Temp (SAFT)	
Flammability	Flammable per industry standard flame projection test

Product Usage

Sabre Grip S10 is designed to be applied to both of the two surfaces to be bonded. Ensure that surfaces are dry and free from dirt, grease, oils and any other solvents. Spray an even ‘web’ of adhesive to cover 80% to 100% of the surfaces. Ensure all edges are coated (window spraying is recommended). Do not allow the adhesive to concentrate or puddle in one area. Allow the adhesive to dry to tack for 2-4 minutes. To test the tack, touch adhesive lightly with the back of your finger. If the adhesive feels sticky but does not transfer to the skin, the adhesive has dried to tack. It is important that no solvent is trapped between the surfaces but that the adhesive is not too dry when bonding. For porous surfaces and crucial areas, it is recommended to apply a second coat after the first has become tacky. Position components carefully, as a strong bond is made immediately on contact. Place the coated surfaces together and apply firm, uniform pressure (20psi is the recommended pressure) to the entire bonding surface ensuring that any air bubbles are expelled (a hand or nip roller is recommended). Full adhesive strength will be reached in 24 hours. To remove excess adhesive use Sabre Grip Citrus based adhesive remover.

Note

Before using, the user shall determine the suitability of the product for their intended use. Use only as directed. Additional information is listed in the Material Safety Data Sheet.

First Aid

Ingestion: DO NOT induce vomiting. Rinse mouth immediately and give 1-2 glasses of water and obtain medical assistance. Should the patient vomit, maintain a clear airway until medical assistance is obtained.

Eye Contact

Wash with water immediately and obtain medical assistance.

Skin Absorption: Wash all affected areas thoroughly with soap and water. Clothing should be laundered before reuse. Seek medical advice for skin irritation.

Inhalation

Carefully remove persons to fresh air, avoid becoming affected yourself. If the person is severely affected obtain medical assistance. If the person stops breathing apply artificial respiration and other first aid techniques as required until medical assistance is obtained. If poisoning occurs, contact Poison Hot Line Australia 131 126, New Zealand 0800 764 766, or visit your doctor.

Spill or Leaks

Wear appropriate protective clothing and equipment. Extinguish all ignition sources. Dam and recover. Prevent entry into drainage systems, rivers and waterways etc. Collect with absorbent materials such as sand, earth or appropriate commercial absorbent. Shovel up with non-sparking tools then place into suitable containers for disposal as per Local / State or Federal Regulations. Empty containers may have product residue. Follow safety procedures until empty container is cleared.

Fire

In case of fire use Carbon Dioxide Foam or Dry Chemical. Do not use Water Jets.

Warnings

For industrial use only. Use in ventilated areas. Do not store above 48°C. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. Keep out of reach of children.

Caution

These materials may be harmful if swallowed or inhaled and may cause skin or eye irritation. Avoid breathing vapour. Use only in well-ventilated areas and wear appropriate personal protection equipment. Avoid contact with skin and eyes. Do not eat, drink or smoke while using. Keep away from heat, sparks, open flames and any other sources of ignition. Do not contaminate water supply. Dispose of empty containers safely. Additional information is listed in the Material Safety Data sheets.



Packaging

12.5kg Disposable Canister

DISCLAIMER OF WARRANTY

Manufacturer and distributor of this product make no warranty, express or implied, including, but not limited to any implied warranty of fitness for a particular purpose. No warranty is made as to the use or effects incidental to such use, handling or possession of the materials herein described. User is responsible for determining whether this product is fit for a particular purpose and method of application and assumes all risk and liability associated herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost at its sole discretion. No representative of ours has authority to change this provision which relates to all sales.

New Zealand

+64 6 366 0007
40-42 Cambridge St South
Levin 5510

Melbourne

+61 3 8657 5507
67 Gateway Blvd
Epping, VIC 3076

Sydney

+61 2 9098 8244
Level 6, 10 Herb Elliott Ave
Sydney Olympic Park, NSW 2127