

Good bonds last.

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: SabreGrip S41 Acoustic Adhesive

Restrictions of use: Refer to Section 15

New Zealand Supplier: Sabre Adhesives Ltd

Address: 42 Cambridge Street South

Levin, 5510, New Zealand

Telephone: +64 (0)6 366 0007

0800 764 766 (National Poison Centre) **Emergency No:**

Australian Supplier: Sabre Adhesives Ltd

Address: Level 6, 10 Herb Elliot Avenue, Sydney, NSW, 2127

Telephone No: +61 2 9098 8244

Emergency No: 13 11 26 (National Poison Line)

Date SDS Issued: 11 March 2019

Section 2. **Hazards Identification**

Australia - Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

NZ - EPA Approval Code: Surface Coatings and Colourants (Flammable) - HSR002662

Pictograms











Flammable Compressed Gas

Irritant

Chronic

Ecotoxic

SIGNAL WORD: DANGER

HSNO Class.	Hazard Code	Hazard Statement	GHS Category
2.1.1A	H220	Extremely flammable gas.	Flam. Gas 1
3.1B	H225	Highly flammable liquid and vapour.	Flam. Liq. 2
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1

Product Name: SabreGrip S41 Acoustic Adhesive Prepared by: Technical Compliance Consultants (NZ) Date of SDS: 11 March 2019 Tel: +64 9 475 5240 WWW.techcomp.co.nz

Page 1

6.3B	H316	Causes mild skin irritation.	Skin Irrit. 3
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.9A	H372	Causes damage to organs through prolonged or repeated exposure.	STOT RE 1
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code Prev	vention Statement
----------------------	-------------------

P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective clothing.

Response Code Response Statement

itesponse code	Response statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	Eliminate all ignition sources if safe to do so.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use dry powder or chemical foam (liquid only)

Storage Code Storage Statement

P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code Disposal Statement

P501 Dispose of according to the local authorities

Section 3. Composition of hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Dimethyl ether	30-60	115-10-6
N'Hexane	30-60	110-54-3
Acetone	5-10	67-64-1

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice.

If on Skin Remove/Take off immediately all contaminated clothing and wash before

reuse. Rinse skin with water/shower. If adhesive bonding occurs, do not force skin apart. If skin irritation occurs: Get medical advice/ attention.

If Swallowed DO NOT induce vomiting. Get medical attention immediately. Move

affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse nose and mouth with water. Never give

anything by mouth to an unconscious person.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: Aspiration hazard if swallowed. May be fatal if swallowed and enters

airways. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May Cause the following effects: Gastrointestinal symptoms, including upset stomach. Central nervous system depression. Nausea, vomiting. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Inhalation: May cause coughing and difficulties in breathing. May cause eye and

respiratory system irritation. Overexposure may depress the central

nervous system, causing dizziness and intoxication.

Skin: May be absorbed through the skin. Product has a defatting effect on skin.

The liquid is irritating to eves and skin. A single exposure may cause the

following adverse effects: Dryness and/or cracking.

Eye: Causes serious eye irritation. Burns can occur. A single exposure may

cause the following adverse effects: Pain. Conjunctivitis, irritation, tearing. Prolonged or repeated exposure may cause the following adverse effects: Irritation of eyes and mucous membranes. Prolonged contact causes

serious eye and tissue damage.

Section 5. Fire Fighting Measures

Hazard Type	The product is extremely flammable. Pressurized container: Must not be
	exposed to temperatures above 50°C. Containers can
	burst violently or explode when heated, due to excessive pressure build-
	up. Vapours are heavier than air and may spread near ground and travel
	a considerable distance to a source of ignition and flash back.
Hazards from	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon
products	dioxide (CO2). Hydrogen chloride (HCI). Nitrous gases (NOx).
Suitable	Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Do
Extinguishing	not use water jet as an extinguisher, as this will spread the fire.
media	
Precautions for	Wear positive-pressure self-contained breathing apparatus (SCBA) and
firefighters and	appropriate protective clothing.
special protective	
clothing	
HAZCHEM CODE	2YE

Section 6. Accidental Release Measures

For personal protection, see Section 8. No smoking, sparks, flames or other sources of ignition near spillage. Evacuate all unnecessary personnel.

Do not discharge into drains or watercourses or onto the ground.

Avoid discharge into drains. Contain spillage with sand, earth or other suitable non-combustible material. Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Section 7. Handling and Storage

Handling:

- Read label before use.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting
- · Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe fumes, vapours or spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Avoid release to the environment.
- Wear protective clothing.
- Avoid contact with skin and eyes.
- Provide adequate ventilation.
- Use approved respirator if air contamination is above an acceptable level.
- Wear protective clothing.

Storage:

- Store locked up.
- Keep away from children.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- Isolate from incompatible materials detailed in Section 10.
- Keep containers tightly closed, in a cool, well ventilated place.

Section 8 Exposure Controls / Personal Protection

Exposure Limit Values:

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

	IWA	SIEL
Substance	ppm mg/m³	ppm mg/m³
Dimethylether (2001) [115-10-6]	400 766	500 958
Acetone (bio) [67-64-1]	500 1,185	1,000 2,375
Hexane (n-Hexane) (bio) [110-54-3]	20 500	
Other isomers	72 1,760	1,000 3500

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or

narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Engineering Controls

This product must not be handled in a confined space without adequate ventilation. Avoid inhalation of vapours and spray/mists. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Personal Protection Equipment







Eyes	Chemical splash goggles or face shield. Avoid wearing contact lenses.
Hands and Skin	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Respiratory	Use protective gloves. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
General	If exposure levels are likely to be exceeded, use a half face mask fitted with an organic vapor filter for short term low level exposures. For long term or high level exposures, a supplied air respirator should be used.

Section 9 Physical and Chemical Properties

Appearance	Aerosol (canister)
Colour	Green
Odour	Not available
Odour Threshold	Not available
pH	Not available
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	Not available
Flammability	Not available
Upper and Lower	Not available
Explosive Limits	
Vapour Pressure	Not available
Bulk Density	Not available
Relative Density	Not available
Solubility in water	Not available
Partition Coefficient:	Not available
Auto Ignition temp	Not available
Oxidising	Not available
Viscosity	Not available
Volatile organic compound	Not available

Section 10. Stability and Reactivity

Stability of Substance	Stable at normal ambient temperatures and when used as recommended.
Conditions to Avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidising agents. Reducing agents.

Incompatible Materials	Oxidising agents. Reducing agents.	
Hazardous Decomposition	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO).	
Products	Carbon dioxide (CO2). Hydrogen chloride (HCl). Nitrous gases	
	(NOx).	

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.	
Dermal	Not applicable.	
Inhalation	Not applicable.	
Eye	Causes severe eye irritation.	
Skin	Causes mild skin irritation.	

Chronic Effects:

Carcinogenicity	Not applicable.	
Reproductive	Not applicable.	
Toxicity		
Germ Cell	Not applicable.	
Mutagenicity		
Aspiration	May be fatal if swallowed and enters airways.	
STOT/SE	Not applicable.	
STOT/RE	Causes damage to organs through repeated or prolonged exposure.	

Section 12. Ecotoxicological Information

New Zealand: HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Biodegradation	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Empty packaging completely prior to disposal. Do not pierce or burn, even

after use. Place any recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in

accordance with local regulations.

Precautions: Ensure waste container containing recovered product is labelled

"Hazardous Waste – Flammable and Ecotoxic". Do not allow to enter

waterways.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in Australia; ADG 7 This product is classified as a Dangerous Good for transport: NZS 5433:2012



Road and Rail Transport

Un No 3501 Class-primary 2.1

Packing Group None Allocated

Proper Shipping Name CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

(DIMETHYL ETHER)

Air Transport

Un No 3501 Class-primary 2.1

Packing Group None Allocated

Proper Shipping Name CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

(DIMETHYL ETHER)

Marine Transport

Un No 3501 Class-primary 2.1

Packing Group None Allocated

Proper Shipping Name CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

(DIMETHYL ETHER)

Section 15 Regulatory Information

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Schedule 5 Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable) - HSR002662

HSNO Classification: 2.1.1A, 3.1B, 6.1E(asp), 6.3B, 6.4A, 6.9A, 9.1B

HSNO Controls in New Zealand:

Trigger quantities for this substance:

	Trigger Quantity
Certified Handler	Not required
Location Certificate	100kg (2.1.1A)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250kg (2.1.1A)
Emergency Response Plan trigger Quantities	300kg (2.1.1A)
Secondary Containment trigger Quantities	300kg (2.1.1A)
Restrictions of use	None

Section 16 Other Information

Glossary

Product Name: SabreGrip S41 Acoustic Adhesive Prepared by: Technical Compliance Consultants (NZ)
Date of SDS: 11 March 2019 Prepared by: Technical Compliance Consultants (NZ)
Tel: +64 9 475 5240 WWW.techcomp.co.nz

Page 7

EC₅₀ Median effective concentration. EEL Environmental Exposure Limit. EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC₅₀ Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD₅₀ Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level WES Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

2. Standard for the Uniform Scheduling of Medicines and Poisons.

3. Australian Code for the Transport of Dangerous Goods by Road & Rail.

4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

5. Workplace exposure standards for airborne contaminants, Safe work Australia.

6. American Conference of Industrial Hygienists (ACGIH).

7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 11 March 2019 Review Date: 11 March 2024