

# SabreSeal™ MB

SabreSeal MB is a one component, non-drying polybutene rubber based mastic that does not harden but rather remains permanently soft and paste-like. SabreSeal MB has excellent resistance to water vapour transmission.

## Features

- Permanently Non-Skinning
- Low Shrinkage
- Moisture Resistance
- Excellent Adhesion

## Uses

It's suitable for all kinds of plastics, metals, glass, masonry and timber. It also can be used in the installation of coolrooms and prefabricated construction.



## Limitations

- Should not be applied in exposed joints
- Not for use in areas subject to dynamic stress
- Not for mobile homes, truck bodies

## Colour

White, Almond. Other colours are available upon request.

## Specification

<b>Form</b>	Non-Sagging Paste
<b>Colour</b>	White
<b>Specific Gravity</b>	1.60 ± 0.05
<b>Slump</b>	2.5 mm Maximum
<b>Shrinkage</b>	5 % Maximum
<b>Service Temp.</b>	- 40° C to 80° C

## Application

- Surface must be clean and dry
- Cut nozzle to desired size
- Insert cartridge into caulking gun
- Push sealant ahead for uniform bead
- Clean off excess sealant with kerosene or mineral spirits

## Caution

Read and understand Material Safety Data Sheet before handling or using this product. We recommend preliminary compatibility tests prior to application to achieve desirable results.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

### New Zealand

+64 6 366 0007  
40-42 Cambridge St South  
Levin 5510

### Melbourne

+61 3 8657 5507  
67 Gateway Blvd  
Epping, VIC 3076

### Sydney

+61 2 9098 8244  
Level 6, 10 Herb Elliott Ave  
Sydney Olympic Park, NSW 2127