

## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: Sabre CC Citrus Cleaner Canister 3.5kg  
 Product Use: Cleaning Agent – For professional use only  
 Restrictions of use: Refer to Section 15

**New Zealand Supplier:** Sabre Adhesives Ltd  
 Address: 42 Cambridge Street  
 Levin, 5510, New Zealand  
 Telephone: +64 (0)6 366 0007  
**Emergency No: 0800 764 766 (National Poison Centre)**

**Australian Supplier:** Sabre Adhesives Ltd  
 Address: Level 6, 10 Herb Elliot Avenue,  
 Sydney, NSW, 2127  
 Telephone No: +61 2 9098 8244  
**Emergency No: 13 11 26 (National Poison Line)**

Date SDS Issued: 3 March 2022

### Section 2. Hazards Identification

**Australia:**  
 Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

**New Zealand:**  
 Classified as hazardous according to Regulation (EC) No. 1272/2008 which meets New Zealand jurisdiction criteria as per EPA Hazardous Substances (Classification) Notice 2020.

**NZ - EPA Approval Code:** Surface Coatings and Colourants (Flammable) - HSR002662

#### Pictograms



**SIGNAL WORD: DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Liquified Gas	H280	Contains gas under pressure may explode if heated.
Flammable Liquids Cat. 3	H226	Flammable liquid and vapour.
Aspiration hazard Cat. 1	H304	May be fatal if swallowed and enters airways.
Skin irritation Cat. 2	H315	Causes skin irritation.

Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment chronic Cat. 2	H411	Toxic to aquatic life with long lasting effects.

**Prevention Code      Prevention Statement**

P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground, bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fumes, gas, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.

**Response Code      Response Statement**

P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder or water fog.

**Storage Code      Storage Statement**

P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

**Disposal Code      Disposal Statement**

P501	Dispose of according to the local authorities
------	---

**Section 3.      Composition of hazardous Ingredients**

Ingredients	Wt%	CAS NUMBER.
Orange Sweet ext	60 - 100	8028-48-6

**Section 4.      First Aid Measures**

Routes of Exposure:

If in Eyes      Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.  
Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention. If adhesive bonding occurs, do not force eyelids apart.

If on Skin It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Continue to rinse for at least 15 minutes. If adhesive bonding occurs, do not force skin apart.

If Swallowed Rinse mouth thoroughly with water. Give plenty of water to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

If Inhaled Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway.  
Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.

**Most important symptoms and effects, both acute and delayed**

Symptoms: See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Eye contact: Bonds skin and eyes in seconds. May cause discomfort. May be slightly irritating to eyes. Indication of any immediate medical attention and special treatment needed

Ingestion: May cause stomach pain or vomiting. May cause drowsiness or dizziness. May cause sensitisation or allergic reactions in sensitive individuals. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Inhalation: Get medical attention. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

Skin: Causes skin irritation. May cause skin sensitisation or allergic reactions in sensitive individuals. Prolonged or repeated exposure may cause the following adverse effects: Dryness and/or cracking. Bonds skin and eyes in seconds.

Notes to Doctor: Treat symptomatically.

**Section 5. Fire Fighting Measures**

<b>Hazard Type</b>	Flammable Liquid / Canister
<b>Hazards from products</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air. Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Harmful gases or vapours.
<b>Suitable Extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Do not use water jet as an extinguisher, as this will spread the fire.

<b>Precautions for firefighters and special protective clothing</b>	In the event of fire, Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents. Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>HAZCHEM CODE</b>	<b>2YE</b>

<b>Section 6. Accidental Release Measures</b>
---

**Personal Precautions:**

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

**Environmental Precautions:**

Collect and place in suitable waste disposal containers and seal securely. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

**Methods and Materials for containment and cleaning up:**

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Approach the spillage from upwind. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Flush away spillage with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

<b>Section 7. Handling and Storage</b>
--

**Handling:**

- For professional users only. Read and follow manufacturer's recommendations.
- Keep away from food, drink and animal feeding stuffs.
- Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Do not handle until all safety precautions have been read and understood.

- Do not handle broken packages without protective equipment.
- Do not spray on an open flame or other ignition source.
- Pressurized container: Do not pierce or burn, even after use.
- Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
- Avoid contact with eyes.
- Keep container tightly closed.
- Ground, bond container and receiving equipment.
- Use explosion-proof electrical, ventilating and lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust, fumes, gas, mist, vapours or spray.
- Wash promptly if skin becomes contaminated.
- Take off contaminated clothing and wash before reuse.
- Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet.
- Change work clothing daily before leaving workplace.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.

**Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Protect from sunlight. Store in a well-ventilated place.
- Store at temperatures between 10°C and 25°C.
- Keep away from oxidising materials, heat and flames.
- Keep only in the original container.
- Keep containers upright. Protect containers from damage.
- Do not store near heat sources or expose to high temperatures.
- Do not expose to temperatures exceeding 50 °C.
- Bund storage facilities to prevent soil and water pollution in the event of spillage.
- The storage area floor should be leak-tight, jointless and not absorbent.

<b>Section 8</b>	<b>Exposure Controls / Personal Protection</b>
------------------	--

**WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance	TWA ppm mg/m <sup>3</sup>	STEL ppm mg/m <sup>3</sup>
-----------	------------------------------	-------------------------------

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2020 12<sup>TH</sup> EDITION.

**Engineering Controls**

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure the ventilation system is regularly maintained and tested. As

this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

### Personal Protection Equipment



<b>Eyes</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
<b>Hands and Skin</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Respiratory</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
<b>General</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

## Section 9 Physical and Chemical Properties

<b>Appearance</b>	Canister – 3.5kg
<b>Colour</b>	Colourless to pale yellow
<b>Odour</b>	Characteristic
<b>Odour Threshold</b>	Not available
<b>pH</b>	Not available
<b>Boiling Point</b>	175°C@ 20 mbar
<b>Melting Point</b>	-96°C
<b>Freezing Point</b>	Not available
<b>Flash Point</b>	46°C (Closed Cup)
<b>Flammability</b>	Extremely Flammable
<b>Upper and Lower Explosive Limits</b>	Not available
<b>Vapour Pressure</b>	2.1mm Hg@ 20°C
<b>Vapour Density</b>	0.01
<b>Bulk Density</b>	838 kg/m <sup>3</sup>
<b>Solubility</b>	Not available
<b>Partition Coefficient:</b>	Not available

Product Name: Everbuild All Purpose Silicon Spray  
Date of SDS: 25 February 2022

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 www.techcomp.co.nz

<b>Auto Ignition Temp</b>	237°C
<b>Oxidising</b>	Not available
<b>Viscosity</b>	Not available.
<b>Kinematic Viscosity</b>	Not available
<b>% Volatile</b>	Not available
<b>Refractive Index</b>	1.473

## Section 10. Stability and Reactivity

<b>Stability of Substance</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to Avoid</b>	Avoid exposing aerosol containers to high temperatures or direct sunlight. Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Incompatible Materials</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
<b>Hazardous Decomposition Products</b>	Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes.

## Section 11 Toxicological Information

### Part A = Non Hazardous

### Part B: Acute Effects:

<b>Swallowed</b>	Not applicable. Due to the physical nature of this product, it is unlikely that ingestion will occur. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not applicable. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.
<b>Eye</b>	Not applicable. Bonds skin and eyes in seconds. May be slightly irritating to eyes. May cause discomfort.
<b>Skin</b>	Causes skin irritation. May cause an allergic skin reaction. Bonds skin and eyes in seconds. May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.

### Chronic Effects:

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Not applicable.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	May be fatal if swallowed and enters airways.
<b>STOT/SE</b>	May cause drowsiness or dizziness.
<b>STOT/RE</b>	Not applicable.

## Section 12. Ecotoxicological Information

Toxic to aquatic life with long lasting effects.

<b>Product:</b>	
<b>Persistence and degradability</b>	No data available.
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
<b>Other adverse effects</b>	No data available

Do not allow to enter waterways,

### Section 13. Disposal Considerations

#### General:

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

#### Disposal Method:

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

**Precautions or methods to avoid:** Avoid release to the environment.

### Section 14 Transport Information

This product is classified as a Dangerous Good for transport in Australia; ADG 7  
This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012



#### Road, Rail, Sea and Air Transport

<b>UN No</b>	3501
<b>Class - Primary</b>	2.1
<b>Packing Group</b>	Not assigned
<b>Proper Shipping Name</b>	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (ORANGE, SWEET, EXT.)
<b>Marine Pollutant</b>	Yes

### Section 15 Regulatory Information

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

**Poison Schedule No: Not Scheduled**

#### New Zealand:

Product Name: Everbuild All Purpose Silicon Spray  
Date of SDS: 25 February 2022

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 www.techcomp.co.nz

Classified as hazardous according to Regulation (EC) No. 1272/2008 which meets New Zealand jurisdiction criteria as per EPA Hazardous Substances (Classification) Notice 2020.

**NZ - EPA Approval Code:** Surface Coatings and Colourants (Flammable) - HSR002662

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500kg
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000kg
Emergency Response Plan	1000kg
Secondary Containment	1000kg
Restriction of Use	Only use for the intended purpose.

## Section 16 Other Information

### Glossary

Cat	Category
EC50	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC50	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD50	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

### References:

#### Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

#### New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2020.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-

date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS  
The information herein is given in good faith, but no warranty, express or implied is made. Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 3 March 2022                      Review Date: 3 March 2027