

# Sabre® Surface Activator

Sabre Surface Activator is a cleaner, degreaser and primer for activating non-porous surfaces, such as plastics, coatings and metals. Improves adhesion of sealants based on silicone, polyurethane and MS Polymers.



## Features

- Liquid, easy application
- To be used as a cleaner / primer on non porous surfaces
- Suitable for silicone, polyurethane and MS Polymer® based sealants and adhesives

## Application Conditions

Preparation of plastics, powdercoatings and other non porous surfaces before bonding and sealing.

## Shelf Life

6 months in unopened packaging, in a cool and dry storage place at temperatures between +5°C and +25°C.

## Technical Characteristics

Base	Solvents and special activating agents
Consistency	Liquid
Specific Gravity	0.78g/ml
Flash Point	13°C

## Application

**Method:** Apply with a clean lint free cloth

**Recommendation:** Apply in one direction. Replace cloth regularly in order to avoid contamination of the surfaces.

By doing so the surface is cleaned, degreased and activated for the application of a sealant. Leave to evaporate for 5 minutes. Apply sealant / adhesive not later than 2 hours after application.

## Surfaces

**Type:** All non porous surfaces.

We recommend preliminary compatibility tests previous to application.

## Health And Safety

Apply the usual industrial hygiene. Wear gloves and goggles.

### REMARKS

Sabre Surface Activator can be applied to a wide variety of non porous substrates. Due to the fact that specific substrates, such as: plastics, polycarbonates, etc, may differ from manufacturer to manufacturer we recommend preliminary compatibility tests.

### New Zealand

+64 6 366 0007  
40-42 Cambridge St South  
Levin 5510

### Melbourne

+61 3 8657 5507  
67 Gateway Blvd  
Epping, VIC 3076

### Sydney

+61 2 9098 8244  
Level 6, 10 Herb Elliott Ave  
Sydney Olympic Park, NSW 2127