

# SabreBond™ HS450

SabreBond HS450 is a high performance permanent bonding & sealing tape incorporating an aggressive acrylic adhesive developed to exhibit excellent adhesion on metals and a wide variety of substrates. Designed to replace spot welds, rivets, liquid adhesives & other permanent fasteners. Ideal for stiffener to panel attachment, signage, refrigeration display units & automotive trim attachment.

## Benefits

- Excellent initial tack
- Excellent weather & U.V resistance
- Permanent high bond (PHB)
- Bonds to high energy substrates including metal, glass & plastics
- Long life application

## Applicable Industries

- Building
- Sign Writing
- Plastic
- Automotive
- Manufacturing & Engineering industries

## Conditions of Use

For best results apply self adhesive tapes between 15°C and 25°C in a dry environment. Application surfaces must be dry and free from dust and particles. Do not apply on surfaces treated or contaminated by anti-adhesives. Do not use paint containing additives which could reduce the adhesive properties. Avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. In cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. Care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

## Tape Storage

Ideally store tape between 15°C and 25°C with a maximum relative humidity of 65%. Always store away from heat sources, avoiding exposure to light and if possible keep in the original packaging. When temperatures are lower than 15°C it is highly recommended to recondition the adhesive tape to normal temperatures (15°C to 25°C) before use.

## Tape Shelf Life

Self-adhesive tapes technical features are generally not permanent but remain at their best for approximately 12 months, if stored according to suggested conditions and by avoiding extreme environmental conditions such as quick and sudden temperature changes, exposure to UV light and high levels of humidity.

### Product Features

Initial adhesion	● ○ ○
Final adhesion	● ● ●
Dimensional stability	● ○ ○
Adhesion on even surfaces	● ● ●
Adhesion on rough surfaces	● ○ ○
Ageing resistance	● ● ●
Weathering resistance	● ● ●
Chemical resistance	● ● ●
Resistance to plasticizers	● ● ○

### Applicability On

Foam	● ○ ○
Rubber	● ○ ○
Fabric	○ ○ ○
Glass/Ceramics	● ● ●
Finished Timber	● ● ○
High energy plastics: PVC, PC, ABS	● ● ●
Low energy plastics: PE, PP	● ○ ○
Metal	● ● ●
Paper/Cardboard	● ○ ○

● ● ● Very suitable   ● ● ○ Suitable   ● ○ ○ Suitable with reductions   ○ ○ ○ Not suitable

Temperature Range (°C)	-40 to +120
Static Shear Strength	> 1000 Hours
Adhesion to Stainless Steel (N/25mm)	60 After 20 Minutes 70 After 80 Hours
Thickness (mm)	0.6 (600 Microns)
Standard Sizes Available	12mm x 33m 18mm x 33m 24mm x 33m Custom sizes available on request

The figures above are based off average results from multiple tests, results may vary + or - 5%.

Reviewed May 2022

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

### New Zealand

+64 6 366 0007  
40-42 Cambridge St South  
Levin 5510

### Melbourne

+61 3 8657 5507  
67 Gateway Blvd  
Epping, VIC 3076

### Sydney

+61 2 9098 8244  
Level 6, 10 Herb Elliott Ave  
Sydney Olympic Park, NSW 2127