

## **VOC Content Test Certificate**

Monday 16<sup>th</sup> October 2023

Supplier: Sabre Adhesives Ltd (40-42 Cambridge St South, Levin, 5510, New Zealand)

Product Description: SabreSeal FRA Intumescent Sealant.

Date Tested: 12<sup>th</sup> October 2023 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960 Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings. ASTM D3960-05 test method is referred in accordance with the laboratory testing guidance from Green Building Council of Australia.

Test Data:

| Specification<br>New Zealand Green Building Council<br>Green Star Design & As Built V1.1-13.1.1B<br>Green Star Interiors V1.1-12.1.1B | SabreSeal FRA Intumescent<br>Sealant  |
|---|---------------------------------------|
| Fire Retardant Sealants and Adhesives:  | 34 grams per litre as VOC content per |
| 250 grams per litre   | material                              |

We hereby certify SabreSeal FRA Intumescent Sealant is below the VOC Content limits of chosen category specified by Green Star Design, New Zealand Green Building Council.

Dr. Vyt Garnys PhD, BSc(Hons) AIMM, ARACI, ISIAQ ACA, AIRAH, FMA Managing Director and Principal Consultant

MATDOUR.

Dr. Tuan Duong PhD, BE (Chemical Engineer) Senior Consultant

is Allah

Travis Hale BSc (Biotechnology) Senior Consultant