



Good bonds last.

BPIR – Building Production Information Requirements SabreSeal NC60 Glazing Silicone

Declaration

Sabre Adhesives Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product Name	Product Code
SabreSeal NC60 Glazing Silicone Translucent 300ml	1400158
SabreSeal NC60 Glazing Silicone Black 300ml	1400161

Product Description

SabreSeal NC60 Glazing Silicone is a high-performance silicone designed for architectural grade glazing. It has been developed to exhibit high tensile strength, fast skin time and offers outstanding long-term adhesion and durability. It cures through exposure to atmospheric moisture, and has excellent UV performance.

Scope Of Use

SabreSeal NC60 is ideally suited to glazing, industrial and automotive sealing, where a high-body sealant is desirable. Applications include fin glazing, structural butt joints, general glazing, frameless shower installations, sealing of laminated and reflective glass, installation of solar panels on most roofs.

New Zealand

+64 6 366 0007
40-42 Cambridge St South,
Levin 5510

Australia

+61 2 9098 8244
Level 6, 10 Herb Elliot Ave,
Sydney Olympic Park, NSW 2127

sabreadhesives.com

Limitations

SabreSeal NC60 is not recommended for following applications:

- Structural glazing in aquarium construction
- Structural glazing applications
- Fully submerged joints
- Certain rubbers where bleeding of plasticiser may occur

Conditions Of Use

Installation of SabreSeal NC60 should be carried out by a competent professional, in accordance with the manufacturer's installation instructions.

The responsibility for using this product in accordance with the application's requirements rests with the user. We recommend consulting our Technical Data Sheet, available at www.sabreadhesives.com

Contribution To Building Code Clauses:

Relevant Code Clauses	Contributions to compliance
B2 Durability – B2.3.1 (a)	Clause B2 DURABILITY: Performance E2.3.2 (b), 15 years and B2.3.1 (c), 5 years, SabreSeal NC60 will achieve a minimum of 15 years of performance.
E2 External Moisture:	Performance E2.3.2. When used as part a suitable cladding system, SabreSeal NC60 will contribute to meeting this requirement.
E3 Internal Moisture:	Performance E3.3.3, E3.3.4, E3.3.5 and E3.3.6, When used as part of the substrate lining or finishing system SabreSeal NC60 will contribute to meet these requirements.
F2 Hazardous building materials	Performance F2.3.1 SabreSeal NC60 does not present a health hazard to people. And satisfies this requirement.

Documentation:

For supporting information refer to

<https://www.sabreadhesives.com/product/sabreseal-nc60-glazing-silicone/>

Contact Details:

Sabre Adhesive Ltd
Legal trading name: Sabre Adhesives Limited
Address: 40- 42, Cambridge Street South, Levin 5510, New Zealand
Website: www.sabreadhesives.com
Email: SalesNZ@sabreadhesives.com
Phone number: +64 6 366 0007
NZBN: 9429033154688

Warnings and Bans:

SabreFix NC60 Glazing Silicone is not subject to any warnings or bans under section 26 of the Building Act 2004.